



Order # LD_____

TECH DATA - TLFR20
Tex-Lam Manufacturing 20 Minute Labeled Doors

To:	Job:
Standards (Meet or Exceed)	AWI Section 1300 SLC7, WMDA IS-1A, WIC Section 20
Maximum Size	4/0 X 9/0 ITS – Warnock Hersey Label
Thickness	1-3/4-inch
Core	MDF Crossbanded Particle Core – Meets LDL-1 specifications.
Stiles	Minimum 1-1/4-inch (Before Trim or Pre-Fit) Hardwood or Softwood As Specified. 2-5/8-inch Softwood Available. Matching Or Comparable Hardwood Edges May Be 2-Ply Construction. Stiles Bonded To Core.
Rails	Minimum 1-7/8-inch (Before Trim or Pre-Fit) Mill Option. Larger Rails Available
Lockblocks	Available Per Specification
Adhesive	Vinyl Acetate Type II Water Resistant
Special Details	Machining for Templated Hardware, Lights, Lights, Louvers, Special Blocking, Dutch Doors and Applied Moldings In Compliance With ITS – Warnock Hersey
Labeling Services	ITS – Warnock Hersey
Guarantee	Interior Doors–Life Of Original Installation.
Factory Finish	Laminate Manufactured By: ↑ Formica ↑ Wilsonart ↑ Nevamar ↑ Other
Hardware	Preparation For Hardware To Your Specifications.