



Order # LD_____

TECH DATA – TLFR45 & TLFR60
Tex-Lam Manufacturing 45 & 60 Minute Labeled Doors

To:	Job:
Standards (Meet or Exceed)	WDMA I.S.-1A; AWI Section 1300; 7 th Edition WIC Section 20; and CS 171-5B
Maximum Size	4/0 X 9/0
Thickness	1-3/4-inch
Core	Non-Combustible, Non-Asbestos Mineral Core. Engineered To Meet Labeling Requirements. All Mineral Core Doors Are Manufactured With Edgebonded Construction.
Stiles	Inner Banding ¾-Inch Thick G.P. Firesstop With A ½-Inch Maximum Wood Outer Laminated Prior To Trimming. Standard Outer Ply is Typically Fir. Matching Edge By Request. Direct Screw Withdraw-1130.4 LBS.
Rails	2-Inch Firesstop Top & Bottom Rail – Standard. All Dimensions Are Prior To Factory Trimming. Larger Rails Available.
Lockblocks	Available Per Specification
Adhesive	Vinyl Acetate Type II Water Resistant
Special Details	Machining for Templated Hardware, Lights, Lights, Louvers, Special Blocking, Dutch Doors and Applied Moldings In Compliance With ITS-Warnock Hersey Regulations & Specifications
Guarantee	Interior Doors–Life Of Original Installation.
Labeling Services	ITS – Warnock Hersey
Factory Finish	Laminate Manufactured By: ┆ Formica ┆ Wilsonart ┆ Nevamar ┆ Other
Hardware	Preparation For Hardware To Your Project Specifications. <i>*Template Required</i>