



Order # LD _____

TECH DATA – TLSCB

Tex-Lam Manufacturing Standard Crossbanded Doors

To:	Job:
Standards (Meet or Exceed)	WDMA I.S.-1A; AWI Section 1300; 7 th Edition WIC Section 20; and CS 171-5B
Maximum Size	4/0 X 9/0
Thickness	1-3/4-inch
Core	MDF Crossbanded Particle Core –Meets LDL-1 and ANSI A208.1 Specifications
Stiles	Minimum 1-1/4-Inch (Before Trim or Pre-Fit) Hardwood or Softwood As Specified. 2-5/8-Inch Softwood Available. Matching or Comparable Hardwood Edges May Be 2-Ply Construction. Stiles Bonded To Core.
Rails	Minimum 1-7/8-Inch (Before Trim or Fit) Mill Option. Larger Rails Available.
Lockblocks	Available Per Specification
Adhesive	Vinyl Acetate Type II Water Resistant
Special Details	Machining for Templated Hardware, Lights, Lights, Louvers, Special Blocking, Dutch Doors and Applied Moldings In Compliance With Project Specifications
Guarantee	Interior Doors–Life Of Original Installation.
Faces	Five-Ply Construction – Particle Core, MDF -.048-Inch HPDL
Factory Finish	Laminate Manufactured By: ↑ Formica ↑ Wilsonart ↑ Nevamar ↑ Other
Hardware	Preparation For Hardware To Your Project Specifications. <i>*Template Required</i>